

Cooke T2.8 Mini S4i

| | 18mm | 25mm | 32mm | 50mm | 75mm | 100mm |
|---|--------------------|---------------------|---------------------|---------------------|---------------------|---------------------|
| T-Stop Range | T2.8-T22 | T2.8-T22 | T2.8-T22 | T2.8-T22 | T2.8-T22 | T2.8-T22 |
| Angular Rotation of Iris Scale | 77° | 77° | 77° | 77° | 77° | 77° |
| Min. Marked Object Distance | 250 mm 10 in | 250 mm 10 in | 300 mm 12 in | 500 mm 20 in | 750 mm 30 in | 900 mm 36 in |
| Close Focus from Lens Front | 80 mm 3 in | 93 mm 4 in | 139 mm 5 in | 311 mm 12 in | 564 mm 22 in | 711 mm 28 in |
| Angular Rotation to MOD Endstop | 300° | 300° | 300° | 300° | 300° | 300° |
| Max. Diagonal Angle of View for Super 35 Format | 80° | 62° | 50° | 34° | 22° | 17° |
| Length from Front of Lens to Lens Mount | 120 mm 4.72 in | 110 mm 4.33 in | 110 mm 4.33 in | 137 mm 5.39 in | 137 mm 5.39 in | 137 mm 5.39 in |
| Max Front Diameter | 110 mm 4.33 in | 87 mm 3.43 in | 87 mm 3.43 in | 87 mm 3.43 in | 87 mm 3.43 in | 87 mm 3.43 in |
| Total Weight | 1.3 kg 2.86 lbs | 1.56 kg 3.44 lbs | 1.60 kg 3.52 lbs | 1.50 kg 3.30 lbs | 1.60 kg 3.52 lbs | 1.60 kg 3.52 lbs |

Specifications are provided for the informational use of our clients and are taken from sources deemed to be reliable, but not guaranteed. Exact specifications may vary due to issues such as firmware or version. Please check with the team at Triode regarding any mission critical specifications before renting any equipment.

<https://triode.tv/contact/> or call 717-455-3940.